

ML320FB DOT MATRIX PRINTER



•••❖ ML320FB •••❖ 9-PIN DOT MATRIX PRINTER

A TRULY VERSATILE PRINTER FOR EFFORTLESS HANDLING OF MULTIPLE PAPER TYPES

With simple styling and a straight paper path the ML320FB is ideal for professional business applications and service industries. It is also suited to industrial applications where users need fast printing on multi-part forms or non-standard sized paper. Easy setting for cut sheets, auto-feeding and auto-parking significantly improve performance and productivity over alternative dot matrix solutions.

MAIN FEATURES OF THE ML320FB PRINTER

- ❖ Ideal for general business use, reception areas and administration
- ❖ Oki's unique, high durability 9-pin print head
- ❖ Up to 360 characters per second print speed
- ❖ 106 column, flatbed dot matrix printer with straight, flat paper path
- ❖ Multi-part continuous and cut sheet paper-handling (original + 4 copies)



OKI

ML320FB DOT MATRIX PRINTER

PRODUCT SPECIFICATION

		ML320FB
General	Number of pins	9
	No. of multi-part forms	5 (one original + 4 copies)
Speed & throughput	High speed draft (12cpi & 10cpi)	360cps; 300cps
	Utility (10cpi)	250cps
	Near letter quality	63cps
	Fastest print speed	360cps
Font & print features	Carriage width (10cpi)	106 columns
	Max. in compressed mode	212 columns
	Character pitch	5/10/12/15/17.1/20 pitch & proportional
	Graphics resolution	Up to 240 x 216 dpi
	Typeface & Font	NLQ-Courier, NLQ-Sans Serif, High Speed Draft, Utility
	Typestyle	Emphasised, Enhanced, Double Width, Double Height, Italics, Bold, Superscript, Subscript, Underline, Overscore
Emulations & interfaces	Printer emulations	Epson FX, IBM ProPrinter
	Standard interfaces	Centronics Parallel
	Optional interfaces	Serial RS 232C/RS 422/Current Loop
Paper-handling	Continuous paper	76–305mm
	Card stock weight	45–189gsm
	First printable line (from top of page)	0.5mm
	Standard	Paper parking, Autoload single sheet, Push tractors
	Optional	Single bin sheet feeder
Physical	Dimensions (HxWxD)	200 x 465 x 343mm
	Weight	12kg
	Memory	Standard buffer 23KB (reduced buffer) 15KB normal
	Noise level	59.5dB(A)
Power	Power requirements	230V AC
	Frequency	50/60Hz
Reliability	Print head life	200 million characters
	Ribbon life	2 million characters (re-inking cartridge)
Supplies life	MTBF	5,000 hours



Only use genuine Oki Original consumables to ensure the best quality and performance from your hardware. Non Oki Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

Oki, Network Solutions
for a Global Society

OKI EUROPE, PART OF OKI ELECTRIC

OKI EUROPE LTD,
CENTRAL HOUSE, BALFOUR ROAD,
HOUNSLOW, MIDDLESEX, TW3 1HY,
UNITED KINGDOM
TEL: +44 (0)20 8219 2190
FAX: +44 (0)20 8219 2199
WWW.OKIEUROPE.COM



As an ENERGY STAR Partner, Oki Europe Ltd has determined that this product meets the ENERGY STAR guidelines for energy efficiency

©2003 Oki Europe Ltd.